

Trade No UL NEC. C(UL) CEC Type	No. of Pairs	Standard Lengths		Std. Unit Lbs. ea.	Insulation Thickness		Nominal O.D.		Max DCR (ohms 110m)	Max DCR Unbal %	Max Cap Unbal (pF/ 100 m)	Freq. (MHz)	Max. Attenu. (dB/ 100m)	Min. NEXT+ (dB)	Min. ACR (dB/ 100m)	Min. ELFEXT (dB/ 100m)	Imp. (ohms)	Min. SRL (dB)
		ft.	m		Inch	mm	Inch	mm										
1590A NEC CM CEC CM	2	1000 3000	304.8 914.4	15.5 50.4	.007	.178	.176	4.47	9.38	5	330	4	4.1	53	49	49	100±15%	23
												10	6.5	47	41	41	100±15%	23
												16	8.2	44	36	37	100±15%	23
												31.25	11.7	39	27	31	100±15%	21
												62.5	17.0	35	18	25	100±15%	18
100	22.0	32	10	21	100±15%	16												
1590R NEC CM CEC CM	4	1000 3000 A-1000	304.8 914.4 U-304.8	27.9 81.8 34.5	.007	.178	.200	5.08	9.38	5	330	4	4.1	53	49	49	100±15%	23
												10	6.5	47	41	41	100±15%	23
												16	8.2	44	36	37	100±15%	23
												31.25	11.7	39	27	31	100±15%	21
												62.5	17.0	35	18	25	100±15%	18
100	22.0	32	10	21	100±15%	16												

Pair No.	Color Combination
1	White/Blue Stripe, Blue
2	White/Orange Stripe, Orange
3	White/Green Stripe, Green
4	White/Brown Stripe, Brown