

ADDITIONAL HEADEND CABLING SOLUTIONS

Quad-shield, RG59 headend cable is used in headend applications which require longer runs or higher bandwidth. It's also available in an 8-pack version, and is equivalent to CommScope HEC-2 cable. See connector sections for compatible F and BNC connectors.

Part Number	Description	Nominal O.D. (in)	Nominal Wt. (lb/1000')
V100177	RG59 Quad Shield, Single HEC2	0.270	35
YR51180	RG59 Quad Shield, 8-pack HEC2	0.997	364

HEADEND CABLE, SINGLE AND 8-PACK

Electrical Characteristics:

Impedance: 75 ± 3 ohms
 Nom. Inductance: .097 Micro-H/ft
 Nom. Capacitance Conductor to Shield: 16.2 pF/ft
 Nom. Velocity of Propagation: 83%
 Nom. Delay: 1.2 ns/ft
 Structural Return Loss: 5 - 1000 MHz, 20 dB Min.
 Max. Operating Voltage: 300 V RMS
 Nom. Conductor DC Resistance @ 20°C: 25.8 ohms/1000'
 Nom. Shield DC Resistance @ 20°C: 6.6 ohms/1000'
 Attenuation:



MHz	5	55	211	270	300	350	400	450	550	750	870	1000
dB/100ft	0.89	1.95	3.59	4.05	4.27	4.64	4.88	5.30	5.90	6.96	7.54	8.09

Physical Characteristics:

Temperature Rating: -40° To +80°C
 Min. Bending Radius: 2.5" (single); 10" (8-pack)
 Max. Pulling Tension: 140 lbs
 Conductor Material & Dia: 20 AWG Solid Silver Plated Copper Covered Steel, .032"
 Dielectric Material & Dia: Gas Injected Foam Polyethylene, .144"
 Shield Type: 1st Layer - Bonded Duofoil
 2nd Layer - 95% Alum Braid
 3rd Layer - Duofoil Tape
 4th Layer - 95% Alum Braid
 U.L./NEC & CEC Rating: CATV or CM; UL-1581 Vertical Tray Flame Test
 Available in 11 colors

CABLE MANUFACTURED EXCLUSIVELY FOR WHITE SANDS ENGINEERING BY

