

Complete more installs faster and better using the Super Buddy™ meter!

Be “sure of your bird” with the positive ID feature or use the automatic scan to identify the unknown satellite.

Tired of loading new satellite plans? Super Buddy’s geo-sensitive “Field Guide” shows you just the birds visible to your install — ALL of them, and their individual transponders.

Navigate easily from bird to bird with left/right arrows and through individual transponders with up/down arrows. It’s the BEST and the EASIEST!

Don’t know the angles for your antenna? The zip code look-up gives you elevation and azimuth for whichever satellite you select.

Multi-switch control? DiSEqC?

“They’re in there”

Durability? “The best”

Voltage/current measurements?

“Of course”

HughesNet cross-pol? “That too”

Signal compatibility?

“DSS, DVB-S, Digicipher 2 and Dish 8PSK. Wow!”

Satellite delivery is becoming more complex, but the Super Buddy makes it easier! Handle the toughest jobs better, faster and cheaper with Super Buddy.

Super Buddy™
Satellite Meter



Why it’s the best:

- Positive ID with ID scan
- Geo-sensitive “field guide”
- Zip code lookup
- Easy operation
- Rugged Durability

“Reliability through Simplicity”

FEATURES

- ID the satellite by “align-to-lock” or “automatic scan”
- Positive ID multi-lock algorithm eliminates false positives
- Field replaceable connectors
- Rugged durable aluminum case with rubber shock guards
- Geo-sensitive “Field Guide” software stores all satellites and transponders per region
- Zip code entry provides antenna azimuth, vertical angle, and tilt/skew settings
- Controls multi-LNBs/switches with 22kHz/DiSEqC
- Large back-lit graphic LCD
- Easy to use single function front panel buttons
- Displays cross-pol value from HughesNet Ku Band modems
- Able to manually enter new satellites using front panel keypad
- Audible tone for signal lock and peak
- Quick charge battery with universal AC or vehicle 12 VDC
- Computer interface for future upgrades
- Store measurements for proof-of-performance “POP Scan”
- Pass/Fail for key transponders “Limit Scan”

MEASUREMENTS

- Signal Level (dBm, dBmV, dBuV) with present and peak bargraph
- Signal Quality, familiar IRD value with present and peak bargraph
- Carrier-to-noise ratio (dB)
- Bit Error Rate (Reed Solomon)
- Voltage supplied by IRD
- Current drawn by LNB
- LNB frequency deviation to check for LNB drift

STANDARD ACCESSORIES

- Shoulder strap
- Cordura protective flap
- AC Line Cord for charging battery (built-in 100 to 240 VAC Transformer)
- Automobile cigarette-lighter adapter battery charge cord
- PC Download cable (USB)
- Operation Manual
- Training video (DVD format)

OPTIONS

- Built-in 21V module for powering DIRECTV SWM-ODU and aligning without power inserter

OPTIONAL ACCESSORIES

- Blue Bunny – voltage converter for Wild Blue installations – tech can align dish before hooking up modem
- SWiM Kick 21 – external voltage converter for DIRECTV SWM-ODU – align dish without power inserter
- NS-1 Broadband Noise Generator – for use with Super Buddy Noise Scan feature to check coax cable integrity

SPECIFICATIONS

Frequency Range	950-2150 MHz
Tuning Resolution	Individual Transponders
Signal Level Range.....	-70 to -10 dBm (-21 to +39 dBmV) (+39 to +99 dBuV)
Level Accuracy	+/-2 dB typical, 3 dB max
Signal Lock Formats	DSS, DVB-S, Digicipher 2, 8PSK Turbo
Impedance	75 Ohm
LNB Power.....	13VDC for V/R, 18VDC for H/L, current limited at 750 mA
Switch Control	22 kHz, DiSEqC, DISH Legacy
Battery	rechargeable NiMH 7.2V, 3.0 Ah
Run time/charge	3 hours for a single LNB (depends on LNB current draw)
Universal AC charger	100 to 240 VAC, 50/60 Hz fast charge and then trickle
Vehicle charger	12VDC
Computer Interface	USB
RF Connector	Double-F barrel field replaceable
Size/Weight.....	6.8"W x 6.4"H x 3.2"D / 2.9 lbs. (without rubber guards) 17.3cm x16.3cm x 5.8cm / 1.3kg
Temperature Range.....	0° to 125°F (-17°C to 51°C)
Warranty	12 month limited

Specifications subject to change without notice.



5230 Elmwood Ave.

Indianapolis, Indiana 46203 USA

Tel: (317) 782-4331 Fax: (317) 786-9665

Toll Free in USA: 1-800-244-2976

<http://www.appliedin.com>

 **APPLIED INSTRUMENTS, INC.**
TELECOMMUNICATIONS INSTRUMENTATION

VISA, MasterCard, Amex, Discover accepted