

BLANK DUCT PLUGS

Sealing Devices for Ducted Cable Networks

Blank duct plugs effectively seal conduits to reduce the cost of cable placement and maintenance in new underground construction projects and routine work. These plugs are economical because they are removable and reusable.

Manufactured from high-impact plastic components, combined with durable elastic gaskets, Blank plugs are corrosion proof and effective as long-term or temporary seals.

Both water-tight and gas-tight, Blank duct plugs prevent the flow of water and the costly sedimentation of duct banks and conduit systems while confining problems of dangerous vapors to their source.

Each Blank plug is equipped with a rope tie device to allow the securing of pull rope to the plug's back compression plate. Installers can attach the rope to the back compression plate of the plug and store excess slack rope behind the plug within the conduit system for future use.



Features

- All plastic construction
- Corrosion proof
- Water-tight
- Easy installation and removal
- Reusable

Part Number	Size	Duct I.D. Range	
		inches	mm
07D100U	0.700	0.71 - 0.83	18.0 - 21.1
10D104U	1.000	0.96 - 1.16	24.4 - 29.5
12D148U	1.250	1.14 - 1.48	29.0 - 37.6
12D163U	1.375	1.30 - 1.63	33.0 - 41.4
15D183U	1.500	1.49 - 1.83	37.8 - 46.5
20D236U	2.000	1.83 - 2.36	46.5 - 59.9
25D296U	2.500	2.34 - 2.96	59.4 - 75.2
30D346U	3.000	2.99 - 3.46	75.9 - 87.9
35D400T	3.500	3.45 - 3.80	86.9 - 96.5
35D400U	3.500	3.45 - 3.80	86.9 - 96.5
35D400N	3.500	3.45 - 3.80	86.9 - 96.5
38D401-C	3.800	3.80 - 3.94	96.5 - 100.1
40D400T	4.000	3.94 - 4.17	100.1 - 105.9
40D402N	4.000	3.94 - 4.17	100.1 - 105.9
40D402U	4.000	3.94 - 4.17	100.1 - 105.9
40D402U-C	4.000	3.94 - 4.17	100.1 - 105.9
50D500U	5.000	4.58 - 5.02	116.3 - 127.5
50D535U	5.000	5.00 - 5.35	127.0 - 135.9
55D590U-CR	5.500	5.51 - 5.91	140.0 - 150.1
60D637U	6.000	5.82 - 6.37	147.8 - 161.8
70D750U-CR	7.000	7.09 - 7.55	180.1 - 191.8
80D816U	8.000	7.83 - 8.27	198.9 - 210.1