

Cable Ready's molding is made of 26 gauge Galvalume steel. Galvalum lasts longer and is more durable than G90 hot dipped steel.

Note: Most 1/2" fittings mount directly onto the CL050 clip

Right Angle Fittings

For 90° angle on a flat surface

Ordering Information

- 1/2" RA050
- 3/4" RA075
- 1" RA100
- 2" RA200

Inside Corner

For 90° angles on inside walls, ceilings

Ordering Information

- 1/2" IC050
- 3/4" IC075
- 1" IC100
- 2" IC200

Outside Corner

For 90° angles on an outside turnaround a corner

Ordering Information

- 1/2" OC050
- 3/4" OC075
- 1" OC100
- 2" OC200

Coupling Fitting

To cover seam when two pieces of molding are joined

Ordering Information

- 1/2" CO050
- 3/4" CO075
- 1" CO100
- 2" CO200

End Cap Fitting

Used to cover the end of a piece of molding

Ordering Information

- 1/2" EC050
- 3/4" EC075
- 1" EC100
- 2" EC200

Tee Fitting

Used to branch off two different directions at 90° angles

Ordering Information

- 1/2" TE050
- 3/4" CT075
- 1" TE100
- 1" Crossing Tee CT100
- 2" TE200

Reducing Fitting

Used to reduce from larger fitting size to a smaller one

Ordering Information

- 1 x 3/4" RD175
- 2 x 1" RD201
- 2" x 2" x 1" Reducing Tee RT221

Offset Adapter

Used to step up or step down fro a trim board. The standard offset is 5/8". Can be trimmed

Ordering Information

- 1" OA1-58
- 2" OA2-58

Bell Adapter

Used to cover up to a hole at the bottom of the bell.

Ordering Information

- 1" BO300
- 2" BO600

Expansion Boot


Used to create an expansion to cover hole when entering a lock box, ceiling or floor

Ordering Information

- 1" BO100
- 2" BO200

Plaster Rings

Used in a pre-wire application, plaster rings offer fast and uniform attachment of wallplates by means of two threaded holes. Available for both 1/2" and 5/8" drywall.



Ordering Information

- | P/N. | Description | Std. Pkg. |
|-------|---------------------|-----------|
| 11226 | for 1/2" drywall UL | 100 |
| 11227 | for 5/8" drywall UL | 100 |