

Ordering Information

Cable Code	No of Pairs	AWG†	Std. Length		Nominal Outside Dia.		Nominal Wt.		Comcode
			ft.	m	in.	cm	lbs./ft.	kg/m	
WG9WR	25	19	5200	1585	1.03	2.64	0.56	0.83	105 187 884
WG9WR	50	19	2600	792	1.42	3.64	0.99	1.47	105 187 892
WG2WR	25	22	6850	2088	0.80	2.05	0.33	0.49	105 185 771
WG2WR	50	22	4560	1390	1.02	2.62	0.55	0.82	105 185 805
WG2WR	100	22	4550	1387	1.35	3.46	0.98	1.46	105 185 854
WG2WR	200	22	2740	835	1.78	4.56	1.80	2.68	105 185 938
WG2WR	300	22	2280	695	2.11	5.41	2.62	3.90	105 185 979
WG2WR	400	22	1520	463	2.44	6.26	3.24	4.82	105 186 001
WG2WR	600	22	1140	378	2.94	7.54	4.88	7.27	105 186 043
WG2WR	900	22	650	198	3.60	9.23	7.08	10.54	105 428 767
WG4WR	25	24	10100	3078	0.70	1.79	0.25	0.37	105 187 462
WG4WR	50	24	6730	2051	0.88	2.26	0.40	0.60	105 187 504
WG4WR	100	24	5050	1539	1.12	2.87	0.67	1.00	105 187 587
WG4WR	200	24	5050	1539	1.48	3.79	1.17	1.74	105 187 645
WG4WR	300	24	3360	1024	1.78	4.56	1.67	2.49	105 187 652
WG4WR	400	24	2520	768	1.97	5.05	2.14	3.19	105 187 678
WG4WR	600	24	1670	509	2.36	6.05	3.14	4.67	105 187 686
WG4WR	900	24	1120	341	2.85	7.31	4.55	6.77	105 187 702
WG4WR	1200	24	840	265	3.24	8.31	5.78	8.61	105 290 746
WG6WR	100	26	6700	2042	0.88	2.26	0.48	0.71	105 188 601
WG6WR	200	26	5740	1750	1.16	2.97	0.85	1.27	105 188 627
WG6WR	300	26	5020	1530	1.39	3.56	1.19	1.77	105 188 312
WG6WR	400	26	4020	1225	1.53	4.18	1.51	2.25	105 188 163
WG6WR	600	26	2230	680	1.90	4.87	2.14	3.19	105 187 694
WG6WR	900	26	1480	451	2.30	5.90	3.08	4.59	105 187 710
WG6WR	1200	26	1030	314	2.63	6.74	4.12	6.13	105 187 744
WG6WR	1500	26	1030	314	2.80	7.18	5.01	7.46	105 187 751

† AWG metric equivalent: 19 Ga = 0.9 mm, 22 Ga = 0.6 mm, 24 Ga = 0.5 mm, 26 Ga = 0.4 mm.

Note: Pulling eyes are not available on these pair sizes