



Norsat SigmaLink™

The new Norsat SigmaLink™ is the latest in a series of transportable satellite terminals. The SigmaLink™ is ideally suited to provide broadband connectivity for base camps or other prolonged missions where assignments are temporary but deployment is protracted. With simple setup and alignment procedures, personnel with minimal training can have the Norsat SigmaLink™ up and transmitting in minutes.



Flexible

- Ku/X/C band capable
- 1.8 M or 2.4 M antenna for greater throughput
- Available with pointing box (SAA) and/or baseband configuration
- Configurable to operate on any commercial satellite at any time

Intelligent

- Quick and simple assembly
- Assisted-acquire via easy-to-use SAA
- Intuitive graphical software interface
- Built-in spectrum analyzer, beacon detector, DVB receiver
- Software control of transmitter

Rugged

- Packaged in ruggedized industrial cases
- Built tough and weatherized for harsh environments
- Shock protected assemblies
- Compliant with military environmental standards



1.8M SigmaLink™ Baseband Variant

System	C-Band		X-Band		Ku-Band	
EIRP G/T	Rx N/A 15.3 dB/K	Tx 53.3 dBW N/A	Rx N/A >19 dB/K	Tx >61 dBW N/A	Rx N/A 23.7 dB/K	Tx 58.3 dBW N/A
Antenna						
Frequency	3.4 - 4.2 GHz	5.85 - 6.425 GHz	7.25 - 7.75 GHz	7.9 - 8.4 GHz	10.95 - 12.75 GHz	13.75 - 14.5 GHz
Midband Gain	35.4 dBi	39.3 dBi	41 dBi	41.7 dBi	45.1 dBi	46.8 dBi
X-pol	30 dB on axis, 23 dB within 1 dB contour	30 dB on axis, 23 dB within 1 dB contour	N/A	N/A	35dB on axis, 23 dB within 1db contour	35dB on axis, 23 dB within 1db contour
Axial Ratio	N/A	N/A	1.5 dB	1.5 dB	N/A	N/A
Sidelobe	ITU 580 / IESS 207		Meets DSCS		Meets IESS 208	
Isolation						
Tx - Rx	-60 dB	N/A	-110 dB	N/A	-85 dB	N/A
Rx - Tx	N/A	-50 dB	N/A	-110 dB	N/A	-30 dB
Reflector Size	1.8m, 4 piece segmented reflector, offset feed		1.8m, 4 piece segmented reflector, offset feed		1.8m, 4 piece segmented reflector, offset feed	
Antenna Travel						
Az	+/- 35 degrees fine adjust		+/- 35 degrees fine adjust		+/- 35 degrees fine adjust	
El	0 - 90 degrees		0 - 90 degrees		0 - 90 degrees	
Pol	+/- 90 degrees		+/- 90 degrees		+/- 90 degrees	
Feed	2-port linear		2-port circular		2-port linear	
Transmit						
	C-Band	X-Band	Ku-Band			
Output Frequency	5.85 - 6.425 GHz	7.9 - 8.4 GHz	13.75 - 14.5 GHz			
Reference	10 MHz	10 MHz	10 MHz			
Reference Level	0 +/- 5 dBm	0 +/- 5 dBm	0 +/- 5 dBm			
Output Power	40 W	175 W	25 W			
@ P1dB						
Gain (typical)	77 dB	84 dB	50 dB			
Spectral Regrowth	-26 dBc @ 44.7 dBm	-26 dBc @ 45.5 dBm	-26 dBc @ 44 dBm			
Receive						
LNB NF	0.5	0.8	0.8			
Reference	10 MHz	10 MHz	10 MHz			
Reference Level	-5 +/- 5 dBm	+2 +/- 5 dBm	+2 +/- 5 dBm			
Phase Noise	-73 dBc/Hz at 1 kHz	-75 dBc/Hz at 1 kHz	-65 dBc/Hz at 1 kHz			
	-83 dBc/Hz at 10 kHz	-85 dBc/Hz at 10 kHz	-75 dBc/Hz at 10 kHz			
	-93 dBc/Hz at 100 kHz	-95 dBc/Hz at 100 kHz	-85 dBc/Hz at 100 kHz			
Input VSWR	2.2 : 1	2.0 : 1	2.2 : 1			
Output VSWR	2.2 : 1	1.5 : 1	2.2 : 1			
Conversion Gain	65 dBm	55 dBm	65 dBm			
Typical						
Output P1 dB	9 dBm	5 dBm	7 dBm			
Power Req	15 - 24 V on IF cable	15 - 24 V on IF cable	15 - 24 V on IF cable			
Current Drain	550 mA	300 mA	200 mA			
Shock Protected Baseband						
8 Rack Unit						
1st shelf (2RU): (RF Distribution Assembly)	Baseband distributes Tx IF from two modems to the SSPA and distributes Rx IF from LNB to modems and SAA					
2nd shelf (1RU): (CDM 625 modem)	SCPC modem (options and features per customer spec)					
3rd shelf (1RU): (CDM 625 modem)	SCPC modem (options and features per customer spec) (future use)					
4th shelf (2RU): (Cisco 2911 router)	Router (options and features per customer spec)					
5th shelf (1RU): (SAA/PS)	SAA Module Contains an integrated spectrum analyzer, received signal strength meter, and DVB receiver PS supplies up to 100W @ 24V (for IDU), up to 400W @ 48V (for SSPA power supply)					
6th shelf (1RU): (AC-Distribution)	Distributes AC throughout rack					
Shock Protected UPS						
6 Rack Unit						
1st shelf (3RU): 2nd shelf (3RU):	Electronics Batteries					
Capacity Universal Input	3000 VA/ 2100W 90 - 264 Volts 47 - 63 Hz					
Output Voltage	120 V					
Reserve Temperature	5 minutes @ full capacity 0 - 40° C					
Ruggedized System Controller						
Operating System	Microsoft(R) XP Tablet Edition					
Screen	264mm Touchscreen XGA LCD, TFT sunlight readable					
Keyboard	87 Key Compact, Sealed					
CPU	Intel® CoreTM Duo Processor L2400 (1.06 GHz)					
Physical	Low power, shock mounted, fully sealed					
MIL-STD 810F	Ruggedized MIL-Spec Laptop 1RU 254mm deep rack enclosure 482 x 44 x 254mm (WxHxD)					
	514.5 I (vibration) 516.5 IV (freefall) 501.4 I & II (stabilized temp.) 503.4 I (sudden changes) 506.4 III (falling or sprayed liquids)					
Indoor Power Supply						
Prime Power	115 / 230 VAC 50 / 60 Hz					
Output Voltage	48V / 24V					
Consumption	< 500 VAAC					
Interfacility Link Cable						
Length	10m (Standard) 30m (Optional) longer lengths available on request					
Environmental						
Operating Temp	-30 to +50 °C (Antenna/RF) 0 to +50 °C (Indoor Equipment)					
Rainfall	50mm/h Operational 100mm/h Survival					
Wind Speed	72km/h Operational 108km/h Survival					
Humidity	100% condensing (Antenna / RF) 5 - 95% non-condensing (Indoor Equipment)					
Packaging						
10 cases total						
Case 1	Pedestal Case	43cm x 73cm x 84cm 29.5kg				
Case 2	Boom/Legs Case	26cm x 46cm x 1.27cm 29.5kg				
Case 3	Reflector Case 1	36cm x 99cm x 1.04cm 40.9kg				
Case 4	Reflector Case 2	36cm x 99cm x 1.04cm 40.9kg				
Case 5	Baseband Case	68.6cm x 61.6cm x 88. 6cm 66.8kg (est.)				
Case 6	UPS Case	68.6cm x 47.3cm x 88.6cm 71.3kg (est.)				
Case 7	X-Band 125W SSPA	51.8cm x 39.3cm x 79.5cm 35kg (est.)				
Case 8	X-Band Feed, LNB, cables	51.8cm x 31.0cm x 79.5cm 24.5kg (est.)				
Case 9	Misc. Equipment	51.8cm x 31.0cm x 79.5cm 24.5kg (est.)				
Case 10	Misc. Equipment	51.8cm x 31.0cm x 79.5cm 24.5kg (est.)				
Online						
	sales@norsat.com					
	www.norsat.com					



Norsat
International Inc.

United States
+1 410 263 8165

EMEA
+336 71 38 72 27

Canada and Rest of World
+1 604 821 2800

Toll Free
+1 800 644 4562

Online
sales@norsat.com
www.norsat.com

1.8M SigmaLink™ SAA Variant

System	C-Band		X-Band		Ku-Band	
EIRP G/T	Rx N/A 15.3 dB/K	Tx 53.3 dBW N/A	Rx N/A 19.6 dB/K	Tx 55.2 dBW N/A	Rx N/A 23.7 dB/K	Tx 58.3 dBW N/A
Antenna						
Frequency	3.4 - 4.2 GHz	5.85 - 6.425 GHz	7.25 - 7.75 GHz	7.9 - 8.4 GHz	10.95 - 12.75 GHz	13.75 - 14.5 GHz
Midband Gain	35.4 dBi	39.3 dBi	41 dBi	41.7 dBi	45.1 dBi	46.8 dBi
X-pol	30 dB on axis, 23 dB within 1 dB contour	30 dB on axis, 23 dB within 1 dB contour	N/A	N/A	35dB on axis, 23 dB within 1db contour	35dB on axis, 23 dB within 1db contour
Axial Ratio	N/A	N/A	1.5 dB	1.5 dB	N/A	N/A
Sidelobe	ITU 58 / IESS 207		Meets DSCS		Meets IESS 208	
Isolation						
Tx - Rx	-60 dB	N/A	-110 dB	N/A	-85 dB	N/A
Rx - Tx	N/A	-50 dB	N/A	-110 dB	N/A	-30 dB
Reflector Size	1.8m, 4 piece segmented reflector, offset feed		1.8m, 4 piece segmented reflector, offset feed		1.8m, 4 piece segmented reflector, offset feed	
Antenna Travel						
Az	+/- 35 degrees fine adjust		+/- 35 degrees fine adjust		+/- 35 degrees fine adjust	
El	0 - 90 degrees		0 - 90 degrees		0 - 90 degrees	
Pol	+/- 90 degrees		+/- 90 degrees		+/- 90 degrees	
Feed	2-port linear		2-port circular		2-port linear	
Transmit						
	C-Band	X-Band	Ku-Band			
Output Frequency	5.85 - 6.425 GHz	7.9 - 8.4 GHz	13.75 - 14.5 GHz			
Reference	10 MHz	10 MHz	10 MHz			
Reference Level	0 +/- 5 dBm	0 +/- 5 dBm	0 +/- 5 dBm			
Output Power @ P1dB	40 W	35 W	25 W			
Gain (typical)	50 dB	65 dB	65 dB			
Spectral Regrowth	-26 dBc @ 46 dBm	-26 dBc @ 45.5 dBm	-26 dBc @ 44 dBm			
Receive						
LNB NF	0.5	0.8	0.8			
Reference	10 MHz	10 MHz	10 MHz			
Reference Level	-2 +/- 5 dBm	+2 +/- 5 dBm	+2 +/- 5 dBm			
Phase Noise	-73 dBc/Hz at 1 kHz	-75 dBc/Hz at 1 kHz	-73 dBc/Hz at 1 kHz			
	-83 dBc/Hz at 10 kHz	-85 dBc/Hz at 10 kHz	-85 dBc/Hz at 10 kHz			
	-93 dBc/Hz at 100 kHz	-95 dBc/Hz at 100 kHz	-95 dBc/Hz at 100 kHz			
Input VSWR	2.2 : 1	2.0 : 1	2.2 : 1			
Output VSWR	2.2 : 1	1.5 : 1	2.2 : 1			
Conversion Gain Typical	65 dBm	55 dBm	65 dBm			
Output P1 dB	9 dBm	5 dBm	7 dBm			
Power Req	15 - 24 V on IF cable	15 - 24 V on IF cable	15 - 24 V on IF cable			
Current Drain	550 mA	300 mA	200 mA			
Satellite Acquisition Assistant						
Includes Inclinometer, Compass, GPS, SA / RSSI, DVB Receiver, Interface with laptop						
						
Outdoor Power Supply						
Prime Power	115 / 230 VAC					
	50 / 60 Hz					
Output Voltage Consumption	24 V DC					
	< 500 VA AC					
						



Norsat
International Inc.

United States
+1 410 263 8165

EMEA
+336 71 38 72 27

Canada and Rest of World
+1 604 821 2800

Toll Free
+1 800 644 4562

Online
sales@norsat.com
www.norsat.com

2.4M SigmaLink™ Baseband Variant

System	C-Band		X-Band		Ku-Band	
EIRP G/T	Rx N/A 18.5 dB/K	Tx 56.6 dBW N/A	Rx N/A 23.5 dB/K	Tx 58.7 dBW N/A	Rx N/A 27.2 dB/K	Tx 61.6 dBW N/A
Antenna						
Frequency	3.625 - 4.2 GHz	5.85 - 6.425 GHz	7.25 - 7.75 GHz	7.9 - 8.4 GHz	10.95 - 12.75 GHz	13.75 - 14.5 GHz
Midband Gain	38 dBi	42.2 dBi	43.7 dBi	44.3 dBi	47.6 dBi	49.2 dBi
X-pol	N/A	N/A	N/A	N/A	-30dB on axis	-30dB on axis
Axial Ratio	3.0	2.3	1.5 dB	1.5 dB	N/A	N/A
Sidelobe Isolation	ITU 580 / IESS 207		Meets DS/CS		Meets IESS 208	
Tx - Rx	-60 dB	0 dBm input	-110 dB	0 dBm input	-110 dB	0 dBm input
Rx - Tx	0 dBm input	-60 dB	0 dBm input	-110 dB	0 dBm input	-35 dB
Reflector Size	2.4m, 4 piece segmented reflector, offset feed		2.4m, 4 piece segmented reflector, offset feed		2.4m, 4 piece segmented reflector, offset feed	
Antenna Travel						
Az	± 35° fine adjust (360° coarse)		± 35° fine adjust (360° coarse)		± 35° fine adjust (360° coarse)	
El	5 - 90°		5 - 90°		5 - 90°	
Pol	± 90°		± 90°		± 90°	
Feed	2-port circular		2-port circular		2-port linear	
Transmit						
	C-Band	X-Band	Ku-Band			
Output Frequency	5.85 - 6.425 GHz	7.9 - 8.4 GHz	13.75 - 14.5 GHz			
Reference	10 MHz	10 MHz	10 MHz			
Reference Level	0 +/- 5 dBm	0 +/- 5 dBm	0 +/- 5 dBm			
Output Power	40 W	40 W	25 W			
@ P1dB						
Gain (typical)	70 dB	70 dB	70 dB			
Spectral Regrowth	-26 dBc @ P1dB	-26 dBc @ P1dB	-26 dBc @ P1dB			
Receive						
LNB NF	0.5	0.8	0.8			
Reference	10 MHz	10 MHz	10 MHz			
Reference Level	-5 +/- 5 dBm	+2 +/- 5 dBm	+2 +/- 5 dBm			
Phase Noise	-73 dBc/Hz at 1 kHz	-75 dBc/Hz at 1 kHz	-65 dBc/Hz at 1 kHz			
	-83 dBc/Hz at 10 kHz	-85 dBc/Hz at 10 kHz	-75 dBc/Hz at 10 kHz			
	-93 dBc/Hz at 100 kHz	-95 dBc/Hz at 100 kHz	-85 dBc/Hz at 100 kHz			
Input VSWR	1.5 : 1	1.3 : 1	1.5 : 1			
Output VSWR	1.3 : 1	1.3 : 1	1.3 : 1			
Conversion Gain Typical	65 dBm	55 dBm	65 dBm			
Output P1 dB	9 dBm	5 dBm	7 dBm			
Power Req	15 - 24 V on IF cable	15 - 24 V on IF cable	15 - 24 V on IF cable			
Current Drain	550 mA	300 mA	200 mA			
Shock Protected Baseband						
Top Rack Unit:	System Controller, Power Supply					
Middle Rack Unit:	Pointing Tools (Spectrum Analyzer, DVB Receiver) SSPA Control and Management					
Bottom Rack Unit:	Ethernet Switch Modem (user supplied)					

Ruggedized System Controller

Operating System	Microsoft(R) XP Tablet Edition
Screen	264mm Touchscreen XGA LCD, TFT sunlight readable
Keyboard	87 Key Compact, Sealed
CPU	Intel® CoreTM Duo Processor L2400 (1.06 GHz)
	Low power, shock mounted, fully sealed
Physical	Ruggedized MIL-Spec Laptop
	1RU 254mm deep rack enclosure
	482 x 44 x 254mm (WxHxD)
MIL-STD 810F	514.5 I (vibration) 516.5 IV (freefall) 501.4 I & II (stabilized temp.) 503.4 I (sudden changes) 506.4 III (falling or sprayed liquids)

Indoor Power Supply

Prime Power	115 / 230 VAC 50 / 60 Hz
Output Voltage	48V / 24V
Consumption	< 500 VAAC

Interfacility Link Cable

Length	10m (Standard) 30m (Optional) longer lengths available on request
--------	---

Environmental

Operating Temp	-40 to +60°C Operational (ODU) -50 to +70°C Survival (ODU)
Rainfall	0 - 50°C (IDU) 50.8mm/h Operational 101.6mm/h Survival
Wind Speed	Up to 45 km/h Operational (no ballast or anchors) 30 Gusting to 45 km/h Operational (ballast or anchors) 96km/h Survival
Humidity	0 - 100% condensing (Antenna / RF) 5 - 95% non-condensing (Indoor Equipment)



Norsat
International Inc.

United States
+1 410 263 8165

EMEA
+33 71 38 72 27

Canada and Rest of World
+1 604 821 2800

Toll Free
+1 800 644 4562

Online
sales@norsat.com
www.norsat.com

2.4M SigmaLink™ SAA Variant

System	C-Band		X-Band		Ku-Band	
EIRP	Rx N/A G/T	Tx 56.6 dBW N/A	Rx N/A 23.5 dB/K	Tx 58.7 dBW N/A	Rx N/A 27.2 dB/K	Tx 61.6 dBW N/A
Antenna						
Frequency	3.625 - 4.2 GHz	5.85 - 6.425 GHz	7.25 - 7.75 GHz	7.9 - 8.4 GHz	10.95 - 12.75 GHz	13.75 - 14.5 GHz
Midband Gain	38 dBi	42.2 dBi	43.7 dBi	44.3 dBi	47.6 dBi	49.2 dBi
X-pol	N/A	N/A	N/A	N/A	-30dB on axis	-30dB on axis
Axial Ratio	3.0	2.3	1.5 dB	1.5 dB	N/A	N/A
Sidelobe Isolation	ITU 580 / IESS 207		Meets DSCS		Meets IESS 208	
Tx - Rx	-60 dB	0 dBm input	-110 dB	0 dBm input	-110 dB	0 dBm input
Rx - Tx	0 dBm input	-60 dB	0 dBm input	-110 dB	0 dBm input	-35 dB
Reflector Size	2.4m, 4 piece segmented reflector, offset feed		2.4m, 4 piece segmented reflector, offset feed		2.4m, 4 piece segmented reflector, offset feed	
Antenna Travel						
Az	± 35° fine adjust (360° coarse)		± 35° fine adjust (360° coarse)		± 35° fine adjust (360° coarse)	
El	5 - 90°		5 - 90°		5 - 90°	
Pol	± 90°		± 90°		± 90°	
Feed	2-port circular		2-port circular		2-port linear	

Transmit				Interfacility Link Cable		
	C-Band	X-Band	Ku-Band	Length	10m (Standard) 30m (Optional) longer lengths available on request	
Output Frequency	5.85 - 6.425 GHz	7.9 - 8.4 GHz	13.75 - 14.5 GHz			
Reference	10 MHz	10 MHz	10 MHz			
Reference Level	0 +/- 5 dBm	0 +/- 5 dBm	0 +/- 5 dBm			
Output Power	40 W	40 W	25 W			
@ P1dB						
Gain (typical)	70 dB	70 dB	70 dB			
Spectral Regrowth	-26 dBc @ P1dB	-26 dBc @ P1dB	-26 dBc @ P1dB			
Receive				Environmental		
	C-Band	X-Band	Ku-Band	Operating Temp	-40 to +60°C Operational (ODU) -50 to +70°C Survival (ODU) 0 - 50°C (IDU)	
LNB NF	0.5	0.8	0.8	Rainfall	50.8mm/h Operational 101.6mm/h Survival	
Reference	10 MHz	10 MHz	10 MHz	Wind Speed	Up to 45 km/h Operational (no ballast or anchors) 30 Gusting to 45 km/h Operational (ballast or anchors)	
Reference Level	-5 +/- 5 dBm	+2 +/- 5 dBm	+2 +/- 5 dBm	Humidity	96km/h Survival 0 - 100% condensing (Antenna / RF) 5 - 95% non-condensing (Indoor Equipment)	
Phase Noise	-73 dBc/Hz at 1 kHz	-75 dBc/Hz at 1 kHz	-73 dBc/Hz at 1 kHz			
	-83 dBc/Hz at 10 kHz	-85 dBc/Hz at 10 kHz	-85 dBc/Hz at 10 kHz			
	-93 dBc/Hz at 100 kHz	-95 dBc/Hz at 100 kHz	-95 dBc/Hz at 100 kHz			
Input VSWR	1.5 : 1	1.3 : 1	1.5 : 1			
Output VSWR	1.3 : 1	1.3 : 1	1.3 : 1			
Conversion Gain	65 dBm	55 dBm	65 dBm			
Typical						
Output P1 dB	9 dBm	5 dBm	7 dBm			
Power Req	15 - 24 V on IF cable	15 - 24 V on IF cable	15 - 24 V on IF cable			
Current Drain	550 mA	300 mA	200 mA			

Satellite Acquisition Assistant

Includes Inclinometer, Compass, GPS, SA / RSSI, DVB Receiver, Interface with laptop



Outdoor Power Supply

Prime Power	115 / 230 VAC 50 / 60 Hz
Output Voltage Consumption	24 V DC < 500 VA AC



Norsat
International Inc.

United States
+1 410 263 8165

EMEA
+336 71 38 72 27

Canada and Rest of World
+1 604 821 2800

Toll Free
+1 800 644 4562

Online
sales@norsat.com
www.norsat.com