

DAC7000

Professional Audio Encoder/Multiplexer



HIGHLIGHTS

- 3/4 SCPC Operation
- 3/4 Codec support includes Industry Standard ISO/MPEG Layer II
- 3/4 Encodes 1 Stereo pair (2 mono)
- 3/4 Balanced Analog and AES/EBU Audio Inputs
- Compatible with all Legacy Radyne ComStream Audio networks including the ABR202/200 and DAC700/400
- Full Featured Front Panel Monitor and Control
- ¾ Headphone Jack Monitor
- 3/4 1 RU Chassis

Description

Tiernan's DAC7000 is the newest and most integrated digital audio encoder in our audio lineup and is compatible with all Radyne ComStream legacy audio products including the DAC700 when serving as an encoder.

The DAC7000 allows operators to save space-segment transmitting narrow-band carriers for each audio stream. By connecting a Modem and transmission equipment to a DAC7000, unlimited audio receivers can be added to complete the network and receive the broadcast.

Industry Standard Encoding

The DAC7000 digitally encodes audio and multiplexes data using industry standard ISO/MPEG Layer II. 7 different audio rates allow the network to select between audio quality and transmission costs. User data along with relay/cue signals can be multiplexed into the encoded audio stream allowing for completely automatic operation at remote sites using the ABR202A, 202 or 200.

SCPC Operation

SCPC (Single Carrier Per Channel) support for networks based on Radyne ComStream's legacy DAC 700/400 codec and ABR202/200 receiver is provided with the DAC7000. The DAC7000 can be used to replace the encoding functionality of the DAC700 or as an additional encoder in a DAC700/400 installation. The DAC7000 is compatible with popular Modems including the Radyne DMD20 and CM701/601 as well as redundancy switches including the Radyne RCS11, CX101, CX801 and AX801.

Applications

Tiernan audio networks are in place in more than 50 countries, sending audio information to customers of such diverse businesses as:

- National radio networks including multiple channels in different languages
- Automated commercial radio distribution networks
- In-store audio networks for retailers with regional advertising



DAC7000

Professional Audio Encoder / Multiplexer



TECHNICAL SPECIFICATIONS

Audio Encoding	
ISO/MPEG Layer II:	• 12:1, 8:1, 6:1 compression factors
-	• 64,96,128,192,256, 384 Kbps
	Mono, Dual Mono (stereo), Joint stereo modes
Audio Ports:	Analog Inputs, L/R Stereo pair, Balanced, DB 9 Female Connector
	Digital Inputs, AES/EBU, Balanced Stereo, DB-15 Female Connector
Auxiliary Data Processing:	 Async Channels: 1200, 2400, 4800, 9600 bps, EIA-232; DB-9 Female Connector
TTL Sensor Inputs	Optically Isolated, 16 Inputs, DB-37 Female Connector
Management & Control:	 RS-232 Proprietary Command Line Monitor & Control (ASCII) or RS-485 Tiernan/ComStream Packet Protocol, DB-9 Female Connector Smart Front Panel Control Status Fault Relay
Physical:	 1RU Standard 19" Rack-Mount – 4.5 cm High x 48.3 cm Wide x 45 cm Deep (1.75" x 19" x 17.7") Weight Less Than 5.5 kg (12 lbs.)
Power Supply:	Auto-Sensing, Auto-Ranging 90-240 VAC, 50-60 Hz Universal Power Supply
Operating Conditions:	Ambient Temperature: 0° to 50°C
Safety & Emissions:	CE Certification
Optional Equipment (sold separately):	DB-9 or DB-15 to XLR Audio Cables

USA/Canada/Latin America: 7330 Trade Street, San Diego, California 92121 USA Tel: +(1) 858.805.7000 Fax: +(1)858.805.7001 3138 East Elwood Street, Phoenix, Arizona 85034 USA Tel: +(1) 602.437.9620 Fax: +(1)602.437.4811 Europe/Middle East/Africa: 13 The Enterprise Centre, Coxbridge Business Park, Alton Road, Farnham, Surrey GU10 5ES, United Kingdom Tel: +(44)1252.731.300 Fax: +(44)1252.716.915

China: Room 405, Building B, Heqiao Mansion, No. 8 Guanghua Road, Chaoyang District, Beijing 100026 China Tel: +(86)10.658.31975 Fax: +(86)10.658.31974

Asia-Pacific: 150 Cecil Street, #80-02, Singapore 069543 Tel: +(65) 6325.1956 Fax: +(65) 6325.1950 Indonesia: 7th floor Wisma budi Suite 702 Jl.H.R. Rasuna Said Kav: C-6, Jakarta, 12940 Indonesia Tel: +(62) 21 521 3733, 252-2676 Fax: +(62) 21 252 0142 Prices, specifications, and availability subject to change without notice.

All trademarks acknowledged. © Copyright 2007 Radyne Corporation. All rights reserved.

