

**CommScope P-3 / Times Fiber T-10**

<b>Cable Series</b>	<b>Part Number</b>	<b>Center Cond.</b>	<b>Outer Cond.</b>	<b>Body Hex (A)</b>	<b>Back Nut Hex (B)</b>
.500	G2-500-CH-P3	.109	.500	1	1
.625	G2-625-CH-P3	.137	.625	1-1/8	1-1/8
.750	G2-750-CH-P3	.167	.750	1-1/4	1-1/4
.875	G2-875-CH-P3	.194	.875	1-3/8	1-3/8

**CommScope QR**

.540	G2-540-CH-QR***	.124	.540	1-1/8	1-1/8
.715	G2-715-CH-QR***	.166	.715	1-1/4	1-1/4
.860	G2-860-CH-QR***	.203	.860	1-3/8	1-3/8

**Times Fiber TX-10**

.565	G2-565-CH-TX	.129	.565	1-1/8	1-1/8
.700	G2-700-CH-TX	.165	.700	1-1/4	1-1/4
.840	G2-840-CH-TX	.194	.840	1-3/8	1-3/8

**Trilogy MC2**

.500	G2-500-CH-MC2	.123	.510	1-1/8	1-1/8
.650	G2-650-CH-MC2	.156	.640	1-1/4	1-1/4
.750	G2-750-CH-MC2	.185	.760	1-3/8	1-3/8

**Early Generations (P1 Cable)**

.500	G2-500-CH-P1	.100	.500	1	1
.750	G2-750-CH-P1	.148	.750	1-1/4	1-1/4

\*\*\* Incorporates a non-metallic support sleeve