

PRODUCT SPECIFICATIONS



AT-A-GLANCE

DEVICE TYPE	Power Distribution Unit
RACK UNIT QUANTITY	1U
OUTLET QUANTITY	2 Front / 10 Rear
AVAILABILITY	Sold Individually

ALTERNATE VIEW (REAR)



VERICOM[®] Rack Mount Power Distribution Unit PDU with 10+2 AC Outlets 1U

We offer this Rack Mount Power Distribution Unit (PDU) as a solution to many of the power management problems seen in today's IT environments. Using only 1U, this PDU features a front panel with 2 AC outlets, a lighted On/Off switch, 3 status indicator lights and 10 additional AC outlets on the back panel and is a great addition to any of our rack or cabinets.

SPECIFICATIONS	
Input Voltage	120V
Input Frequency	60Hz
Maximum Input Current	15A
Plug Type	NEMA 5-15P
Plug Style	Straight
Cord Length	5 ft (1.5 m)
Cord Specs	14 AWG 3-Wire Grounded SJT
Output Voltage	120V
Output Frequency	60Hz
Output Wattage	1800W
Circuit Breaker / Overload Protection	15A
Maximum Continuous Operating Voltage	130V
Outlet Quantity	2 Front / 10 Rear
Outlet Type	NEMA 5-15R
Surge Suppression	700 Joules
Protection Mode	N-H, N-G, H-G
Response Time	<1 Nanosecond
Maximum Surge Current	10KA
Maximum Surge Voltage	470V
Clamping Voltage	775V
EMI/RFI Filtration	40~60dB@10MHz
PDU Style	Rack Mount 1U)
Pre-Installed Rack Mount Brackets	Removable
Housing Material	PVC and Metal Enclosure
Product Dimensions (HxWxD)	1.75" x 17.5" (without ears)
Product Weight	3.5 lbs.
Inner Carton Quantity	1 Unit
Inner Carton Dimensions (LxWxH)	3.6" x 21.25"x 2.5"
Inner Carton Weight	3.71 lbs.
Master Carton Quantities	10 pcs.
Master Carton Dimensions (LxWxH)	13.78" x 21.65"x 11.61"
Master Carton Weight	N/W: 35 lbs. G/W: 37.1 lbs.
UL Certified Power Cord	Yes
RoHS	Yes
Operating Temperature Range	-40° to 70°
Operating Humidity	≤95%

ITEM NO.	RACK UNIT QUANTITY
RAPDUH11	1U

NOTE: TECHNICAL SHEETS ARE SUBJECT TO CHANGE WITHOUT NOTICE.