

# 915CL OPTICAL FIBER CLEAVER

Fast, Accurate and Reliable Fiber Cleaving

## SPLICE AND CLEAVE FIBER THE RIGHT WAY!

### FAST

Cleaved Fiber remains in the adapter ready to splice and is compatible with the 910FS or the lighter, 915FS model.

### ACCURATE

Precision-engineered blades accurately cleave fibers for minimal loss.

### RELIABLE

Field tested to perform the dust bin safely collects end cuts.



# 915CL

## OPTICAL FIBER CLEAVER

FOR PRODUCT VIDEOS,  
DEMONSTRATIONS AND MORE VISIT:  
[www.youtube.com/GreenleeDEMO](http://www.youtube.com/GreenleeDEMO)

### BENEFITS

- **Accurate Cleaves.** Cleave multi-mode and single-mode fiber optic cables.
- **Long Life.** Blades rotate for longer life - over 48,000 cleaves.
- **Adaptable.** Supports 250um, 900um fibers and loose tube fibers.
- **Fast.** For use with the 910FS or the 915FS Optical Fusion Splicer for maximum speed and efficiency with auto return mechanism.
- **Dust bin.** Safely collects end cuts during cleaving process.
- **Fixed Clamp.** Allows the technician to use the 915CL as a standalone cleaver.



915FS

FOR USE WITH THE 910FS OR 915FS  
FUSION SPLICERS

### SPECIFICATIONS

APPLICABLE FIBERS	SM (G.652); MM (G.651); DS (G.653); NZDS (G.655); BIF (G.657)
FIBER CLEAVED LENGTH	10mm
CLADDING DIAMETER	125µm
COATING DIAMETER	0.25 mm and 0.9 mm
FIBER COUNT	Single
CLEAVING ANGLE	≤ 1.5°
BLADE LIFE	48,000 Cleaves
WEIGHT	0.56 lbs (255 g)
DIMENSIONS (HxWxD)	2.29 x 2.17 x 1.89" (58 x 55 x 48 mm)

### ORDERING INFORMATION

CAT NO.	UPC NO.	DESCRIPTION
915CL	06864	915CL Optical Fiber Cleaver
01640	01640	Cleaving Wheel
915FS	06672	915FS Optical Fusion Splicer
01332	01332	250µm Adapter (Pair)
01333	01333	900µm Adapter (Pair)
05801	05801	Loose Tube Adapter (Pair)
03245	03245	3mm Adapter (Pair)

CAT NO.	UPC NO.	DESCRIPTION
PA1171	12225	ProGrip 5-in-1 Fiber Optic Stripper
PA1177	12228	ProGrip 3-in-1 Fiber Optic Stripper
10997	10997	Economy Fiber Optic Stripper
PA1511	03120	Kevlar Cutter
MSS100	05712	Mid Span Slitter
07111	07111	Fixed Clamp for 915CL with Screw

The 915CL is supplied with a fixed clamp and a mounting screw that the technician can use to permanently mount the fixed clamp to the cleaver. Shipped not assembled.

**For more information or to order, contact TVC Communications**  
**888.644.6075 • [www.tvcinc.com](http://www.tvcinc.com)**



[www.greenleecomunications.com](http://www.greenleecomunications.com) MA6580 REV 09/16

©2016 Greenlee Textron Inc. • An ISO 9001 Company • Printed in USA  
Greenlee Textron Inc. is a subsidiary of Textron Inc.