


ALL-IN-ONE PRODUCT



ROTATING BLADE LIFE
UP TO **75,000**



ELECTRODE LIFE
UP TO **38,000**



BENEFITS AND FEATURES

Integrates 5 functions in one unit (stripping, cleaning, cleaving, splicing and protecting)

The fusion splicer with All-In-One system provides the best workability on the pole and limited work spaces

No scratches on fiber by thermal stripping

Compatible with Fusion Splice-On Connector (FSOC) in accordance with the industrial standard

Ideal for enterprise, data centers, broadband and FTTH network application

UPGRADE OPTION

VFL (Visual Fault Locator) utilizes a 650nm red laser to locate and visibly display any failure points throughout the cable

InGaAs Power Meter (indium, gallium, arsenide) detects the amount of power lost during transmission and can help correct potential errors




STRIPPING



CLEAVING



CLEANING



FUSION SPLICE-ON CONNECTORS



SPECIFICATIONS

KF4A

| CATEGORY | DESCRIPTION |
|-----------------------------------|--|
| Fiber alignment | IPAAS Clad to Clad Alignment |
| Applicable type of fibers | 0.25mm; 0.9mm; 2.0mm; 3.0mm Indoor cable |
| Fiber count | Single fiber |
| Applicable fiber dimensions | Cladding diameter: 125 μ m; Coating diameter: 150 μ m~3mm |
| Fiber setting and cleaved length | 0.20in to 0.63in |
| Splicing modes | Splice mode: 300; Heat mode: 100 |
| Typical splice Loss | SM: 0.02dB; MM: 0.01dB; DS:0.04dB; NZDS: 0.04dB |
| Return loss | > 60dB |
| Splicing time | Typical 7sec. with SM |
| Splice loss estimate | Available |
| Sleeve heating time | Typical 13sec. with IS-60 mode, IS-60 sleeve |
| Applicable protection sleeve | 40mm (2.4in); 60mm (1.5in) micro sleeves |
| Storage of splice result | Data: up to 5,000ea; Image: up to 5,000ea |
| Tension test | 1.96N to 2.25N |
| Operating condition | Altitude: 0~5,000m above sea level, Temperature: -14°F~122°F, Humidity: 0~95%, Wind: 15m/s, non-condensing, dust proof, water proof, shock proof |
| Storage condition | Temperature: -40°C~80°C (40°F~176°F); Humidity: 0~95% |
| Dimension | 132(W) x 212(L) x 73(H)mm (without rubber protector) |
| Weight | 1.5kg (Including battery) |
| Viewing method and display | 2 AXIS Two CMOS cameras with 109mm (4.3in) color LCD monitor |
| Fiber view and magnification | X/Y: 110X; Max:220X |
| Power supply | Li-ion battery (DC 14.8V, 3400mAh); 100 ~ 240V AC Charger |
| No. of splice cycles with battery | Typical 200 cycles |
| Electrode life | Up to 38,000 splices |
| Blade life | Up to 75,000 fibers |
| Terminals | USB |



STANDARD PACKAGE

| CATEGORY | MODEL | Q'ty |
|----------------------|----------------------|--------|
| Arc fusion splicer | SWIFT KF4A | 1 |
| Battery | KF-3400 | 1 |
| Battery adapter | FY1701000 | 1 |
| Instructions for use | - | 1 |
| Spare electrode | EI-24 | 1 pair |
| Transporting case | HC-11 (hard case) | 1 |
| Optical fiber holder | - | 1 pair |
| Cooling tray | CT-01 (40mm (1.5in)) | 1 |
| Allen wrench | LD-3300 | 1 |
| USB cable | - | 1 |
| Hard brush | - | 1 |
| Soft brush | - | 1 |
| Tool box | - | 1 |
| Tweezer | - | 1 |



OPTION PACKAGE

| CATEGORY | MODEL |
|----------------------|--|
| Battery | KF-3400 |
| Cleaver blade | BI-07 |
| Electrode | EI-24 |
| Transporting case | ILST-SS03(L) (soft case) |
| Work belt | WB-01 |
| Sleeve | S09-C, S09, S30-C, S30 |
| Sleeve clamp | SC-01 |
| SOC connector | SC, LC, FC, ST (refer to FTTx solution catalogue) |
| Manual stripper | CF-02 |
| External power | DC 12V (available for car cigar jack) |
| Optical fiber holder | HS-250, HS-900, HS-2.5, HS-IN, HF4-SC/FC, HF4-ST, HF4-ILC, LS-900 (choose one) |

* Design, standard/optional package and specification shown above are subject to change with or without notice.