

Audio/Video Modulator

BAVM-860SAW

Headend



○ Features & Benefits

- Meets FCC Docket 21006 Aeronautical Frequency Offset Requirements
- Fully Compatible With BTSC Encoded Stereo Audio
- Front Panel Accessible Level Controls for Easy Set-Up and Adjustments
- Low Cost High Performance Channelized Audio/Video Modulator
- AC Convenience Outlet

The Blonder Tongue BAVM-860SAW is an economical commercial quality TV modulator. It provides a +55 dBmV RF output on any specified CATV channel from 2 to 135 (54 to 860 MHz). HRC and IRC frequency plans are also available. The BAVM-860SAW is ideal for placing A/V program sources such as satellite receivers, VCR's, DVD's, cameras or TV demodulators onto standard 6 MHz NTSC TV channels for broadband distribution. The BAVM-860SAW features IF SAW filtering with built-in FCC group delay pre-distortion assuring excellent adjacent channel performance and color operation. The modulator complies with FCC 21006 with +/- 5 KHz visual carrier stability and required frequency offsets on all aeronautical channels. For BTSC stereo applications, a field-defeatable audio pre-emphasis network is provided making the BAVM-860SAW compatible with any out-board stereo generator that provides a composite baseband output. A -30 dB output test point and all user controls are provided on the front panel.

○ Specifications

RF

Frequency Range: CATV Channels 2 to 135
Output Level: 55 dBmV, Min
Output Level Range:
15 dB, Continuously Adjustable by Front Panel Output Level Control
Audio/Video Carrier Ratio Control:
-7 dB to -20 dB,
Frequency Tolerance:
±10 kHz - Standard Channels
±5 kHz FCC 21006 Offsets
Audio Carrier Frequency Setting:
±1 kHz, Max
4.5 MHz Above Video Carrier
RF to Video Response from Fv -0.5 MHz to Fv +4.2 MHz: 1 dB P/V
Broadband Noise -90 dBc
Spurious Output in 50 – 860 MHz Range @ +55 dBmV Output: -60 dBc
Output Match (Return Loss): 12 dBc
Vestigial Sideband Response:
@Channel Edge -20 dB
@Adjacent Channel -40 dB

Video

Input for 87.5% Modulation:
0.7V to 2.5 V P-P
Video Input Return Loss: 18 dB
Video Carrier-To-Noise Ratio in 4 MHz Bandwidth: 62 dB
P-P Video to 60 Hz RMS Hum Ratio: 60 dB

Differential Gain at 87.5% Modulation: ≤ 5%
Differential Phase at 87.5% Modulation: ≤ 5°
Group Delay: 170 ± 50 nS

Audio

Input Impedance: 10K Ω, Unbalanced
Input for 25 KHz Peak Deviation: 140 mV RMS
Audio Frequency Response:
±1.0 dB
(50 Hz to 15 KHz ref to std 75 msec Pre-emphasis)
4.5 MHz Intermodulation Stability: ±5.0 kHz

General

Power Requirements:
105-130 VAC, 60 Hz, 10.5 W
Temperature Range: 0 to +50 °C

Mechanical

Dimensions (W x H x D):
19 x 1.75 x 3 in.
482.6 x 44.45 x 76.2 mm
Line Cord:
3 Wire Grounded,
3 Wire Convenience Outlet
Weight: 4 lbs., 1.81 kg

Connectors

Audio In: "F" Female
Video In: "F" Female
RF Out: "F" Female
RF Output Test - 30 dB: "F" Female

Refer to product instruction manual for additional specification measurements and notes.

○ Ordering Information

| Model | Stock No. | Description |
|-------------|-----------|---|
| BAVM-860SAW | 5990 300 | Channelized Audio/Video Modulator, SAW Filtered 54-300 MHz |
| BAVM-860SAW | 5990 860 | Channelized Audio/Video Modulator, SAW Filtered 300-860 MHz |