

PRODUCT
SPECIFICATIONS

Detail Photos

(on right from top to bottom)

Pre-assembled Az/EI Mount

Fine-elevation adjustment
with stamped degree scale

Ku feed assembly with LNB
cover



The reflector is thermoset-molded for strength and surface accuracy.



84 cm Elliptical Receive-Only Antenna System

TYPE 845

The ASC Signal 84 cm Type 845 Elliptical Antenna is a rugged commercial grade product suitable for the most demanding applications. The reflector is thermoset-molded for strength and surface accuracy.

Molded into the rear of the reflector is a network of support ribs which not only strengthens the antenna, but also helps to sustain its critical parabolic shape.

The pole mount is constructed from heavy-gauge steel to provide a rigid support to the reflector. A specially formulated powder paint process offers excellent protection from weather related corrosion.

- All materials comply with EU directive No. 2002/95/EC (RoHS).
- One-piece thermoset-molded offset reflector.
- Factory pre-assembled Az/EI mount.
- Plated hardware for maximum corrosion resistance.

SPECIFICATIONS

Type 845 84 cm Elliptical Receive Only Antenna System

RF Performance

Effective Aperture	84 cm Elliptical (33 in)
Dimensions of Reflector	102 cm x 77 cm
Operating Frequency	10.95 - 12.75 GHz
Polarization	Linear
Gain @ 11.95 GHz	39. dBi
3 dB Beamwidth	1.8°
Antenna Noise Temperature @ 30° El	25° K
VSWR	1.3:1
Cross-Polarization Discrimination (Linear)	30 dB on Axis
Feed Interface	WR75 Flat Flange

(All specifications typical)

Mechanical Performance

Reflector Material	Glass Fiber Reinforced Polyester	
Antenna Optics	One-Piece Offset Feed Prime Focus	
Mount Type	Skew over Elevation over Azimuth	
Elevation Adjustment Range	5° - 90° Continuous Fine Adjustment	
Azimuth Adjustment Range	360° Continuous	
Polarization (Skew) Adjustment Range	±90° Continuous	
Mast Pipe Interface	60 mm (2.38 in)	
Wind Loading	Operational	80 km/h (50 mph)
	Survival	200 km/h (125 mph)
Temperature	-50°C to 80°C	
Humidity	0 to 100% (Condensing)	
Atmosphere	Standard Hardware Meets 500 Hour Salt Spray Test Requirements (ASTM B-117)	
Solar Radiation	360 BTU/h/ft ²	
Shock and Vibration	As Encountered During Shipping and Handling	



ASC Signal Corporation
620 North Greenfield Parkway
Garner, NC 27529 USA

Telephone: +1-919-329-8700

Fax: +1-919-329-8701

Internet: www.ascsignal.com

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

ASC-VSAT25

© 2007 ASC Signal Corporation